



Wideband VHF/UHF Dipole Manpack Antenna WD2250G

The WD2250G is a lightweight wideband dipole antenna with a small visual signature. The antenna does not require a ground plane for proper operation in the 225 – 512 MHz frequency range. Its ideal performance in the NATO I frequency band makes it very well suited for use with modern SDRs, providing effective coverage for a range of voice and data communications.

- Excellent performance over the entire 225 512 MHz frequency range
- · Low weight antenna with flexible gooseneck and tape radiator
- No ground plane required

| Product details* | | |
|-------------------|--|--|
| Frequency range | 225 - 512 MHz | |
| Matching | Passive | |
| Polarization | Nominally vertical | |
| Antenna type | Wideband dipole | |
| Radiation pattern | Omnidirectional | |
| Gain | Measured patterns on request | |
| VSWR | ≤ 3.0 | |
| Nominal Impedance | 50 Ω | |
| Power rating | 20 W (RMS) | |
| Standard color | Black | |
| Radiator | Flexible gooseneck and tape radiator (Ø 22 mm) | |
| Height | 620 mm | |
| Weight | 220 g | |

| Installation* | | |
|---------------|----------------------------------|--|
| RF connection | Male TNC-type connector | |
| Mounting | Directly to a matching connector | |

*Specific adjustments on request

| Order number | Product |
|--------------|------------------------------------|
| WD2250G | Antenna as described above |
| WD2250G-C0 | Antenna with male N-type connector |

ed in this