

The antenna AD-22/G-HP Rev. A is a high power of log-periodic dipole antenna covering the frequency range from 400 to 6000 MHz. The antenna is mainly intended for use for broadcast, EMC applications, radio monitoring, jamming, etc.

The antenna is composed of a boom element and 19 dipoles. All dipole elements and boom are made of brass, protected with silver plating. Dipoles are enclosed in a special housing made of fiberglass. The antenna support on the end enables mounting on masts with outer diameter between 1" (26 mm) and 2" (60 mm). The antenna could be used as transportable or as stationary.

Frequency range	400 - 6000 MHz
Impedance	50 ohm
VSWR	typ. < 2.5
Gain	typ. 8 dBi
Front-to-back ratio	> 15 dB typ.
E-plane 3 dB beamwidth	> 30°
H-plane 3 dB beamwidth	> 40°
Polarization	HOR./VER.
Maximum power:	
at 400 MHz	2750 W CW
at 3 GHz	950 W CW
at 6 GHz	600 W CW
Connector	N female
Length	981 mm
Width	450 mm
Mass	5.8 kg
Wind velocity	160 km/h
Temperature range	-40...+65°C
(Operating)	
Temperature range	-55...+75°C
(Storage)	
IP rating	IP 65
Default color	RAL 6041

