

FreeMile 60

Fiber-Like Speed In Urban Connectivity



License free microwave radio

- ✓ Unlicensed, TDD Technology
- ✓ 60 GHz Frequency
- ✓ Point to point & Multipoint
- ✓ Data Encryption
- ✓ Max 3 Gbps Capacity
- ✓ Up to 6 Km / 3.5 Miles

Specification

Radio

Architecture	Modular design: Outdoor unit + optional antenna kit
Operating Modes	Access Point; Station
Max STA count per AP	Up to 32 stations
EIRP	Outdoor unit: 38 dBm
Frequency Range	57 – 71 GHz (Channels: 1 - 6)
Channel Size	Full: 2.16 GHz; Half: 1.08 GHz
Outdoor Unit	Beamforming 90° x 50° (azimuth x elevation); Antenna gain: 16 dBi
100 mm Antenna Kit	Beamforming 6° x 6° (azimuth x elevation); Gain: 33 dBi
300 mm Antenna Kit	Beamforming 2° x 2°; Gain: 42 dBi
45° Scanning Antenna Kit	Beamforming 45° x 10°; Gain: 30 dBi
90° Scanning Antenna Kit	Beamforming 90° x 10°; Gain: 30 dBi
Range	PTP: up to 6 km (300 mm antenna kit) PTMP: up to 1.6 km (Station with 100 mm antenna kit)
Modulation	MCS1 - MCS12
Encryption	AES + GCMP
Duplexing	TDD

Ethernet Data Parameters

Number Of Ports	1x 10/1000/2500 Eth. (RJ-45) (PoE-In) 1x 10/100/1000 Eth. (RJ-45) (PoE-Out)
VLAN	Data & Management VLAN
Management	HTTP/HTTPS, SSH, SNMP v1(traps only)/v2/v3; RESTful API
Ethernet Data Throughput	Up to 2.3 Gbps (half duplex)

Mechanical

Dimensions	130 x 120 x 55 mm
Temperature	-30 °C to +55 °C / -22 °F to +131 °F
Weight	425 g

Power

Power Consumption	8-17 W, and 41 W with PoE out in use
Power Input	Active PoE 38-57 VDC (Passive injector included)

Solutions

IoT Communications



Last Mile Internet



CCTV



For more detailed information about FreeMile products visit www.freemile.com or contact SAF Tehnika sales info@saftehnika.com.
Product features may vary between different models and configurations.
They are subject to change without prior notice. © SAF Tehnika

AUTHORIZED USA DISTRIBUTION BY:

Cyntony Corporation
195 Follen Road
Lexington, Massachusetts
sales@cyntony.com
781-430-0675

cyntony
customer attuned