

Spectrum Core 10-3000 MHz

J0SSAM31 datasheet

v.1.1 09.10.2024



Your RF Spectrum Analyzer Development Kit For Easy Integration with Your System

Frequency Sweep • Channel Power • Zero-Span

www.spectrumcompact.com

**AUTHORIZED
USA RESELLER:**

Cyntony Corporation
195 Follen Road
Lexington, Massachusetts
sales@cyntony.com
781-430-0675

cyntony
customer attuned

Description:

Spectrum Core is a spectrum analyzer development kit that is perfectly suited for integration with third-party systems. Control of the device and measurement results are obtained by a virtual COM port via a USB interface. Spectrum Core is operator system agnostic and PC can communicate directly to the Spectrum Core without the need for any intermediate software or hardware.

Measurement Setup:

- **Frequency sweep:** Start/Stop
- **Single sweep, Continuous sweep**
- **Power-in-Band**
- **Span:** Full Span, Min Span, Selected Span, Zero-Span
- **Resolution Bandwidth, Video Bandwidth (RBW, VBW)**
- **Attenuation**
- **Low noise amplifier (LNA) ON/OFF**
- **Detector:** Minimum, Average, Maximum

Functions:

- **Power in Band**
- **Sweep:** Continuous, Manual Trigger
- **Zero-Span**

Best for integration:

- **Lightweight and small form factor**
- **Open API**
- **Adaptable physical fixing options**

Frequency

Frequency Range	10 – 3 000 MHz
Frequency Resolution	10 kHz
Frequency Reference	
Aging	±1.0 ppm/1 year
Accuracy (t: 25 °C ± 2.5 °C) + aging	±2.5 ppm
Frequency span	RBW to full range, Zero-Span
Resolution Bandwidth (RBW)	10/30/100/300 kHz
Video Bandwidth (VBW)	1/3/10/30 kHz

Sweep time	
RBW: 10 kHz; Span: 0.5 MHz	<= 335 ms
RBW: 300 kHz; Span: 15 MHz	<= 130 ms

SSB Phase Noise t = 20 °C to 30 °C; F _c = 1 GHz	
Carrier Offset: 20 kHz	-70 dBc/Hz
Carrier Offset: 100 kHz	-90 dBc/Hz
Carrier Offset: 1 MHz	-110 dBc/Hz

Level

Measurement Range	DANL to +20 dBm
Dynamic Range, REF = 0	>= 75 dB
Second Harmonics Distortion <i>ATT: 0 dB, LNA: ON, Input Level: -40 dBm</i>	< -43 dBc typ.
Third-Order Intercept (TOI) <i>ATT: 0 dB, LNA: ON</i>	-5 dBm typ.

Input related spurs	LNA ON
<i>ATT: 0 dB, LNA: ON, REF: -52 dBm; Input level: -50 dBm</i>	< -43 dBc

Amplitude Accuracy <i>ATT: 0 dB ; Detector: AVG ; Input: -50 dBm CW ; RBW, VBW: AUTO</i>	
20 °C to 30 °C (68 °F to 86 °F)	± 1 dB
-15 °C to 55 °C (5 °F to 131 °F)	± 3 dB

Maximum Safe Input <i>Level DC voltage: 0 V</i>	LNA ON	LNA OFF
<i>ATT: 0 dB</i>	+10 dBm	+20 dBm
<i>ATT: 30 dB</i>	+25 dBm	+25 dBm

Typical Actual DANL <i>ATT: 0 dB, Detector: AVG REF: -12 dB Termination 50 Ω Trace: 16AVG, 20 °C to 30 °C</i>		LNA ON	LNA OFF
<i>RBW: 10 kHz; VBW: 1 kHz</i>	10-30 MHz	< -123 dBm	< -103 dBm
	30-3000 MHz	< -125 dBm	< -105 dBm
<i>RBW: 30 kHz; VBW: 1 kHz</i>		< -123 dBm	< -107 dBm
<i>RBW: 100 kHz; VBW: 3 kHz</i>		< -119 dBm	< -102 dBm
<i>RBW: 300 kHz; VBW: 10 kHz</i>		< -114 dBm	< -98 dBm

Typical DANL Normalized to 1Hz		LNA ON	LNA OFF
<i>20 °C to 30 °C, ATT = 0 dB, Termin.: 50 Ω Detector: AVG, Trace: 16AVG</i>	10-30 MHz	< -163 dBm/Hz, typ.	< -143 dBm/Hz, typ.
	30-3000 MHz	< -165 dBm/Hz, typ.	< -145 dBm/Hz, typ.

General Data

Data and Power Interface <i>Input voltage</i>	USB Type-C 5 VDC, 3A
Additional Power input	USB Type-C 5 VDC, 3A
Operating temperature	-33 °C to 55 °C (-27 °F to 131 °F)
Dimensions	135 x 84 x 28 mm 5.32 x 3.31 x 1.1 inch
Weight	0.40 kg / 14.11 oz
Ingress Protection	IP54

RF Input

Impedance	50 Ω (nom.)
Connector	SMA F
VSWR	< 1.5
Input attenuator	0, 5, 10, 15, 20, 25, 30 dB

www.spectrumcompact.com

Spectrum Core 10-3000 MHz PRELIMINARY datasheet

Product features may vary between different models and configurations. They are subject to change without prior notice.

For more detailed information about SAF products visit www.saftehnika.com or contact your SAF representative info@saftehnika.com.
Product features may vary between different models and configurations. They are subject to change without prior notice.