

VERSION: 1.3

Wideband Manpack High-Power Antenna

420 - 2700 MHz

Product Code: OMNI-A0148

SPECIFICATIONS:

Electrical:	
Frequency range	420 – 2700 MHz
Gain	1 dBi typical (in band)
Azimuth pattern	Omni, 1 dB ripple
Polarisation	Vertical
Nominal impedance	50 Ω
VSWR	< 2.5:1 or better
Power handling	20 W CW
Connector	N-type male at base
Mechanical:	
Dimensions (I x d)	650 mm x 40 mm
Total mass	0.5 kg
Mounting	On N-type connector at base
Colour	Black, others on request
Environmental: designed to meet the following specifications	
Temperature range	Storage: -41 °C to +71 °C
	Operation -31 °C to +55 °C
Weatherproofing	IP66 water resistant
	(when mounted on a connector)
Shock and vibration	MIL-STD-810E 516.4:
	Vibration category 8, shock 40 g
Exposed materials	Polymer

PRODUCT OVERVIEW:

The OMNI-A0148 is a vertically polarised wideband omnidirectional antenna with low VSWR and high-power handling for operation in the 420 to 2700 MHz frequency range.

PRODUCT DESCRIPTION:

The OMNI-A0148 is based on a bicone radiator, requiring no additional ground plane for operation. The antenna is integrated into our high strength durable polymer housing which provides excellent operational performance advantages including low visibility, quiet impact noise and flexibility for dealing with obstructions such as door frames and low hanging branches.

The antenna is provided with an N-connector mounted on the base of the antenna for direct mounting to the structure or manpack used.

PRODUCT FEATURES:

- Wideband operation
- High-power handling
- Low VSWR

APPLICATION AREAS:

- Manpack and vehicular signal interception
- Manpack and vehicular communications
- Manpack and vehicular monitoring















Wideband Manpack High-Power Antenna

<u>420</u> – 2700 MHz


Product Code: OMNI-A0148 VERSION: 1.3

Measured VSWR and gain graphs:

Typical VSWR:



GAIN:



Elevation pattern (normalised):

Elevation Pattern - OMNI-A0148

